

01

## FIRST

|                                                                                                     |                                                                                                                                                                                  |                                                                                                       |                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CONSTRUCTION<br>STRUCTURE<br>STRUKTUR<br>STRUCTUUR                                                  | Tufted 1/10" Loop<br>Tufté 1/10" Bouclé<br>Getuftet 1/10" Schlinge<br>Getuft 1/10" Luspool                                                                                       | FIRE RESISTANCE<br>COMPORTEMENT AU FEU<br>BRENNVERHALTEN<br>BRANDGEDRAG                               | EN 13501-1<br>B <sub>fl</sub> s1                                                                                                                                                                                                                                                                                 |
| PILE MATERIAL<br>COUCHE D'USURE<br>POLMATERIAL<br>POOLMATERIAAL                                     | 100% PA6 Solution Dyed Xelux™ Color                                                                                                                                              | FASTNESS TO LIGHT<br>SOLIDITÉ À LA LUMIÈRE<br>LICHTECHTHEIT<br>LICHTECHTHEID                          | ISO 105-B02<br>≥7                                                                                                                                                                                                                                                                                                |
| SECONDARY BACKING<br>DOSSIER<br>RÜCKENAUSSTATTUNG<br>RUG                                            | Back2Back: Modified bitumen<br>enhanced with a thermoplastic elastomer,<br>reinforced with a glass fibre fleece<br>covered with 100% PES fleece<br>10% recycled content included | RUBBING FASTNESS<br>SOLIDITÉ AU FROTTEMENT<br>REIBECHTHEIT<br>WRIJFECHTHEID                           | EN ISO 105-X12<br>≥4                                                                                                                                                                                                                                                                                             |
| TOTAL WEIGHT<br>POIDS TOTAL<br>GESAMTGEWICHT<br>TOTAAL GEWICHT                                      | Ca. 4300 g/m <sup>2</sup>                                                                                                                                                        | COLOUR FASTNESS TO WATER<br>SOLIDITÉ À L'EAU<br>WASSERECHTHEIT<br>WATERECHTHEID                       | EN ISO 105-E01<br>≥4                                                                                                                                                                                                                                                                                             |
| PILE WEIGHT<br>POIDS DU VELOURS<br>POLEINSATZGEWICHT<br>POOLGEWICHT                                 | Ca. 540 g/m <sup>2</sup>                                                                                                                                                         | THERMAL RESISTANCE<br>RÉSISTANCE THERMIQUE<br>WÄRMEDURCHLABWIDERSTAND<br>WARMTEDOORLAATWEERSTAND      | ISO 8302<br>0.047 m <sup>2</sup> K/W                                                                                                                                                                                                                                                                             |
| PILE ABOVE BACKING<br>POIDS DE VELOURS UTILE<br>POLNUTZSCHICHTGEWICHT<br>NUTTIG POOLGEWICHT         | Ca. 330 g/m <sup>2</sup>                                                                                                                                                         | IMPACT NOISE RATING<br>ISOLATION PHONIQUE<br>TRITTSCHALLVERBESSERUNGMAß<br>GELUIDSISOLATIE            | ΔL ISO 140-8<br>37 dB                                                                                                                                                                                                                                                                                            |
| TOTAL HEIGHT<br>ÉPAISSEUR TOTALE<br>GESAMTDICKE<br>TOTAAL DIKTE                                     | Ca. 6,4 mm                                                                                                                                                                       | SOUND ABSORPTION<br>ABSORPTION PHONIQUE<br>SCHALLABSORPTIONSGRAD<br>GELUIDSABSORPTIE                  | ISO 354<br>Hz 125 250 500 1000 2000 4000<br>S 0,01 0,04 0,07 0,19 0,29 0,34                                                                                                                                                                                                                                      |
| PILE HEIGHT<br>ÉPAISSEUR DU VELOURS<br>POLDICKE<br>POOLHOOGTE                                       | Ca. 2,9 mm                                                                                                                                                                       | PERMANENT ANTISTATIC<br>ANTISTATIQUE PERMANENT<br>PERMANENT ANTISTATISCH<br>PERMANENT ANTISTATISCH    | ISO 6356<br>≤2 kV                                                                                                                                                                                                                                                                                                |
| PILE DENSITY<br>DENSITÉ DU VELOURS<br>POLROHDICHTE<br>POOLDICHTHEID                                 | Ca. 0,114 g/cm <sup>3</sup>                                                                                                                                                      | TRANSVERSAL RESISTANCE<br>RÉSISTANCE TRANSVERSALE<br>DURCHGANGSWIDERSTAND<br>DOORGANGSWEERSTAND       | ISO/DIS 10965<br>≤10 <sup>9</sup> Ohm                                                                                                                                                                                                                                                                            |
| TUFT DENSITY<br>NOMBRE DE TOUFFES<br>NOPPENZAHL<br>AANTAL PUNTEN                                    | Ca. 156.000 /m <sup>2</sup>                                                                                                                                                      | SIZE & PACKING<br>DIMENSION & EMBALLAGE<br>ABMESSUNG & VERPACKUNG<br>VERPAKKINGEN & AFMETINGEN        | 50 cm x 50 cm<br>box: 5m <sup>2</sup><br>pallet: 20 boxes                                                                                                                                                                                                                                                        |
| CLASSIFICATION<br>CLASSEMENT<br>KLASSIFIKATION<br>CLASSIFICATIE                                     | EN 1307<br>33 - LC1                                                                                                                                                              | NUMBER OF COLOURS<br>NOMBRE DE COLORIS<br>ANZAHL DER FARBEN<br>AANTAL KLEUREN                         | 12                                                                                                                                                                                                                                                                                                               |
| CASTOR CHAIR SUITABILITY<br>EMPLOI CHAISE À ROULETTES<br>STUHLROLLENEIGNUNG<br>ROLSTOELGESCHIKTHEID | EN 985<br>A : continuous use                                                                                                                                                     | DIMENSIONAL STABILITY<br>STABILITÉ DIMENSIONNELLE<br>DIMENSIONSSTABILITÄT<br>DIMENSIONELE STABILITEIT | EN 986<br>max. 0,20 %                                                                                                                                                                                                                                                                                            |
| DONNÉES ENVIRONNEMENTALES                                                                           | Démarche HQE® : cf. FDES<br>suivant NF P01-010<br>Déclaration du 30/07/2003                                                                                                      | GUT-NR                                                                                                | 24226                                                                                                                                                                                                                                                                                                            |
|                                                                                                     |                                                                                                                                                                                  | BRE                                                                                                   | ENP 428                                                                                                                                                                                                                                                                                                          |
|                                                                                                     |                                                                                                                                                                                  | LEED                                                                                                  | Product contributes toward satisfying Credit 4.3<br>under LEED®. Products are not reviewed under<br>LEED. LEED credit requirements cover the<br>performance of materials in aggregate, not the<br>performance of individual products of brands.<br>Fore more information on LEED, visit<br>www.usgbc.org/contact |
| CLASSEMENT UPEC<br>N° CERTIFICAT NF-UPEC                                                            | U <sub>3</sub> P <sub>3</sub> E <sub>1</sub> C <sub>0</sub><br>329T-006.1                                                                                                        |                                                                                                       |                                                                                                                                                                                                                                                                                                                  |

